

## CMW Extreme Synthetic Blend Motor Oil

Description:

CMW Extreme Synthetic Blend Motor Oil is a premium-quality, synthetic blend, API SJ motor oil designed for use in passenger cars, vans, sports utility vehicles and light trucks under all operating conditions. It is formulated to provide excellent wear protection, to minimize engine sludge and to resist viscosity and high-temperature thermal breakdown. It also protects against rust, bearing corrosion and foaming. The Extreme Synthetic Blend formulation provides an extra margin of protection at both low and high temperatures compared with conventional all-mineral motor oils.

- Friction-modified for improved fuel economy
- Formulated to help protect vehicle emissions control systems
- Resists viscosity and thermal breakdown at high temperatures
- Protects against engine sludge and varnish deposits
- Excellent wear protection
- Excellent rust and bearing corrosion protection

Typical Inspections:

Grade, SAE	5w30	10w30	20w50
Gravity, °API	30.8	30.3	28.4
Flash Point, °F	410	430	465
Pour Point, °F	-29	-22	-29
Viscosity			
cSt @ 40°C	65	70	189
cSt @ 100°C	10.4	10.5	19.6
CCS, °C/cp	-25/2890	-20/3200	-10/4300
Viscosity Index	140	131	128
TBN	6.2	6.2	6.2
Sulfated Ash, wt. %	0.64	0.64	0.64
Copper, wt. %	0.01	0.01	0.01