



TECHNICAL DATA

Product Tech

©2008

Hydraulic Tractor Fluid (UTF)

Description:

CMW Hydraulic Tractor Fluid (UTF) is a multifunctional fluid specially formulated to use in transmissions, final drives, wet brakes and hydraulic systems of equipment employing a common fluid reservoir. High quality base oils are blended with a V.I. improver and special additives to control wear, corrosion, oxidation, foaming and brake chatter. CMW Hydraulic (UTF) has demonstrated excellent performance in all manufacturers' equipment and these OEM's now only approve each of their own fluids. It has good compatibility with other fluids and exceeds Allison recommendations for C4 torque fluids. Because CMW Hydraulic Tractor Fluid (UTF) is a multigrade product, high temperature stability is enhanced by excellent low temperature pumpability.

Exceeds OEM Specifications for John Deere, Case New Holland, Massey-Ferguson, Kubota, and Allison C-4, among others.

Typical Inspections:

SAE Grade	10w20 (approx.)
Gravity, °API	29.3
Viscosity	
cSt @ 40°C	57.9
cSt @ 100°C	9.2
SUS @ 100°F	279
SUS @ 210°F	56.1
Viscosity Index	135
Flash Point, °F	420
Pour Point, °F	-25
Color D-1500	3.5
Brookfield Viscosity, cp @ 0°F	4,250

CMW Oil Company
12929 Telegraph Road Unit H, Santa Fe Springs, CA 90670
(562) 903-4571 phone (562) 903-0622 fax
www.cmwoil.com